

PRODUCT-DETAILS

# 6131/40-24-500

## 6131/40-24-500 KNX Motion Detector Sky W



### Informações gerais

Tipo de produto alargado	6131/40-24-500
ID do produto	2CKA006132A0350
EAN	4011395185971
Descrição do catálogo	6131/40-24-500 KNX Motion Detector Sky W

Descrição longa	<p>Detection range (for mounting height 6 m and 12 m): circular. Walking persons Ø: max. 18 m and 24 m. Visible height 23 mm. With 2 channels. Targeted for connection and disconnection of lights bands depending on the room brightness. Use of the device as a movement detector. Detectors application with 2 power off stages. Detectors application with integrated monitoring function. Constant light switch with up to two independent channels. Constant light switch with max. 2 outputs for brightness-dependent switching of two light bands in the area. With integrated KNX bus coupler.</p> <p>The programming button can be activated with the IR transmitter 6010-25 (-500). Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm. Suitable for surface mounting installation. Cannot be installed in British Standard or VDE flushmounted box. Recommendation: Installation housing from Kaiser HaloX-O (Art.no. 1290-40) with corresponding cover plates (1290-47 or 1290-85 for fair faced concrete) or IBTronic H120-68 from Spelsberg.</p>
-----------------	---

### Installation

Instruções e Manuais	No document needed
----------------------	--------------------

## Circular Value

Circular Design Principles Lifetime	2CKA000073B5454
Group Waste to Landfill Target	No non-hazardous waste is sent to a landfill
Sustainable Material Content in Packaging	FSC Recycled Paperboard - 90 %
Improved Resource Efficiency for Customers	Digital Efficiency - Product is digitally-supported to optimize usage and eventually optimize customer asset
Offered with Extended Lifetime	Product Upgradability
Offered with Takeback Services	Take Back for Recycling

## Eco Transparency

Environmental Product Declaration - EPD	9AKK108468A1033
---	-----------------

## Technical

Ficha de dados, informação técnica	2CKA006132D0202
Intervalo de medição	24 m
Number of Channels	2
Compatible Bus Systems	KNX (TP)
Product Range	KNX
Minimum Switching Time	Switch-On 10 second [unit of time]
Tipo de apoio	Surface Mounted Flush Mounted
Acabamento de superfície	Surface protection: Untreated Surface finishing: Matt
Material	Thermoplastic
Posição de montagem	Ceiling
Model Number	Movement sensor
RAL Number	RAL 9016 - Traffic White
Color	studio white matt
Number of Batteries	0
Application Function	Electrical Load and Light Control

## Environmental

Temperatura do ar ambiente	Operation -5 ... +45 °C
Grau de proteção	IP20
Estado RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informação RoHS	2CKA200000E4528
REACH Declaration	2CKA309999E9999
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

## Dimensions

Largura Líquida do Produto	91 mm
Altura Líquida do Produto	91 mm
Profundidade/Comprimento Líquidos do Produto	45 mm
Peso Líquido do Produto	110.5 g
Built-In Depth (t <sub>2</sub> )	22 mm

## Ordering

ID de Substituição do Produto (ANTIGA)	6132-0-0350
--	-------------

## Certificates and Declarations

Declaração de conformidade -CE	2CKA100000E1061
--------------------------------	-----------------

## Classifications

ETIM 8	EC001582 - Movement sensor for bus system
ETIM 9	EC001582 - Movement sensor for bus system
Categoria REEE	5. Small Equipment (No External Dimension More Than 50 cm)
REEE B2C / B2B	Business To Consumer
CN8	8536 50 80
eClass	V11.0 : 27143144

## Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CKA006132A0403	6131/38-24-500 Intermediate ring fm box W	6131/38-24-500	1	piece
2CKA006899A2304	Protection Cover	6898	1	piece

## Categorias

Produtos e Sistemas de Baixa Tensão → Building and Home Automation Solutions → KNX → Presence Detection → Presence Detectors

