

PRODUCT-DETAILS

SBR-F-10.0.1-83

SBR-F-10.0.1-83 RTC, 10gang, silver



Informações gerais

Tipo de produto alargado	SBR-F-10.0.1-83
ID do produto	2CKA006220A0859
EAN	4011395314500
Descrição do catálogo	SBR-F-10.0.1-83 RTC, 10gang, silver
Descrição longa	Control element with room temperature controller function. For controlling commercially available actuating drives in combination with free@home Heating-/Fan-Coil Actuators. With display of set-value and current temperature. For transmitting switching, push-button, dimming and blind commands to an ABB-free@home® actuator. With integrated bus coupler. With labelling field. Number of bus subscribers: 1

Installation

Instruções e Manuais	2CKA000073B5345
----------------------	-----------------

Technical

Número de LEDs	1
Compatible Bus Systems	free@home (TP)
Product Range	free@home
Tipo de apoio	Flush Mounted

Acabamento de superfície	Surface protection: Lacquered Surface finishing: Matt
Material	Plastic
RAL Number	RAL 9006 - White Aluminium
Color	aluminium silver
Number of Batteries	0
Application Function	Blind / Shutter / Shading Control Electrical Load and Light Control Room Climate Control

Environmental

Temperatura do ar ambiente	Operation -5 ... +45 °C
Grau de proteção	IP20
Estado RoHS	Following EU Directive 2011/65/EU
Informação RoHS	2CKA100000E4679
REACH Declaration	2CKA309999E9999
Classe de temperatura predefinida	I
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Largura Líquida do Produto	90.1 mm
Altura Líquida do Produto	167.1 mm
Profundidade/Comprimento Líquidos do Produto	44.2 mm
Peso Líquido do Produto	163 g
Built-In Depth (t ₂)	30.7 mm

Classifications

ETIM 8	EC001101 - Room temperature controller for bus system
ETIM 9	EC001101 - Room temperature controller for bus system
Categoria REEE	5. Small Equipment (No External Dimension More Than 50 cm)
REEE B2C / B2B	Business To Consumer
CN8	9032 10 20
eClass	V11.0 : 27143133

Categorias

Produtos e Sistemas de Baixa Tensão → Building and Home Automation Solutions → free@home → User Operation → ABB-Tenton® → 10 fold, RTC

