



## 204.WD21D-T23A

### WALL BOX 2 SOCKETS WITH LOCK

Type 2 3P+N+E 32A 400V~ 22kW Type 3A  
1P+N+E 16A 230V~ 3,7kW 32A 400V 3P+N+E  
IP54 IK10

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Commercial series	LIBERA Series	IEC 61439-7 (2018)	[International Standard] Low-voltage switchgear and controlgear assemblies - Part 7: Assemblies for specific applications such as marinas, camping sites, market squares, electric vehicle charging stations
Type of product	WALL BOX 2 SOCKETS WITH LOCK		
Synthetical description	WALL BOX 2 SOCKETS WITH LOCK	EN IEC 61851-1 (2019)	[European Standard] Electric vehicle conductive charging system - Part 1: General requirements
Material	ENGINEERING PLASTIC	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
EV standard	Type 3A 1P+N+E 16A 230V~ 3,7kW	DIRECTIVE EMC 2014/30/UE	[European Directives] Electromagnetic Compatibility Directive
EV standard	Type 2 3P+N+E 32A 400V~ 22kW		
Rated current	32A		
Rated voltage	400V		
Working frequency	50/60Hz		
Poles	3P+N+E		
Protection degree IP	IP54		
Working temperature	-30°C/+50°C		
GLOW WIRE	GW 650°C		
Protection degree IK	IK10		
Colour	GREY		
Mounting version	SURFACE MOUNTING		
Dimensions	360x780x264mm		