



590.EL4012.SN

INTERRUPTOR DE MANIOBRA

40A 1P+SN IP66/IP69 110x150x87mm Y1 IK09
GENERAL AMARILLO/ROJO SN (SOLID NEUTRAL) BLOQUEABLE ON-OFF GW 650°C

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Tipo de producto	INTERRUPTOR DE MANIOBRA	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Serie comercial	Serie ISOLATORS-TP	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Descripción	INTERRUPTOR DE MANIOBRA	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Material	POLÍMERO TÉCNICO	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Grado de protección IP	IP66/IP69	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Tipo	GENERAL	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Color	AMARILLO/ROJO	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Intensidad nominal	40A		
Polos	1P+SN		
Tamaño interr.	Y1		
Tensión nominal	250V		
Dimensiones	110x150x87mm		
Notas	SN (SOLID NEUTRAL)		
Notas	BLOQUEABLE ON-OFF		
Prueba del hilo incandescente	GW 650°C		
Grado de protección IK	IK09		