



590.GEB16003

INTERRUPTOR DE MANIOBRA

160A 3P IP55 BS 370x450x180mm KF2 IK08
GENERAL GRIS/NEGRO FUSE: BS GW 650°C

Product Approvals

TECHDATA		STANDARDS AND LAWS	
Serie comercial	Serie ISOLATORS-TP	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Tipo de producto	INTERRUPTOR DE MANIOBRA	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Descripción	INTERRUPTOR DE MANIOBRA	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Material	POLÍMERO TÉCNICO	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Grado de protección IP	IP55	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Tipo	GENERAL		
Color	GRIS/NEGRO		
Intensidad nominal	160A		
Polos	3P		
Tamaño interr.	KF2		
Tipo de fusible	BS		
Tensión nominal	690V		
Dimensiones	370x450x180mm		
Notas	FUSE: BS		
Prueba del hilo incandescente	GW 650°C		
Grado de protección IK	IK08		