



408.1679

PRESA INTERBLOCCATA

16A 3P+N+T 4h 100-130V 50Hz 60Hz
103X230MM Morsetti a vite Con interblocco meccanico

Certificati

TECHDATA		NORME E LEGGI	
Serie commerciale	PRX	EN 60309-1 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Tipologia prodotto	PRESA INTERBLOCCATA	EN 60309-2 (1999)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Descrizione sintetica	PRESA INTERBLOCCATA		
Tipo installazione	INCASSO		
Corrente nominale	16A	EN 60309-1/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Poli	3P+N+T	EN 60309-2/A1 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Riferimento Orario	4h		
Tensione nominale (range)	50-200V	EN 60309-4 (2007)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock
Tensione nominale	100-130V		
Frequenza d'impiego	60Hz	EN 60309-1/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
Frequenza d'impiego	50Hz	EN 60309-2/A2 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations
Colore	GIALLO		
Materiale	TERMOPLASTICO		
Grado di protezione generico	Stagno all'immersione	EN 60309-4/A1 (2012)	[European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock
Grado di protezione IP	IP66/IP67/IP69		
Grado di protezione IK	IK10	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Morsetti	Morsetti a vite	DIRECTIVE RoHS 2011/65/EU	[European Law] Restriction of the use of certain hazardous substances in electrical and electronic equipment
Materiale di contatto	CuZn (ottone)		

Flangia	103X230MM
Opzioni	Con interblocco meccanico
Note	CON BASE PORTAFUSIBILI
Tipo fusibile	gG 10,3x38mm
Lucchetto	ø5mm