



408.32872

PRESA INTERBLOCCATA

32A 3P+N+T 2h >50V >300-500Hz 103X230MM

Morsetti a vite Con interblocco meccanico

Certificati

| TECHDATA | | NORME E LEGGI | |
|------------------------------|-----------------------|-----------------------------------|---|
| Serie commerciale | PRX | EN 60309-1 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Tipologia prodotto | PRESA INTERBLOCCATA | EN 60309-2 (1999) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Descrizione sintetica | PRESA INTERBLOCCATA | | |
| Tipo installazione | INCASSO | | |
| Corrente nominale | 32A | EN 60309-1/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Poli | 3P+N+T | EN 60309-2/A1 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Riferimento Orario | 2h | | |
| Tensione nominale (range) | 50-200V | EN 60309-4 (2007) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock |
| Tensione nominale | >50V | | |
| Frequenza d'impiego | >300-500Hz | EN 60309-1/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements |
| Colore | VERDE | EN 60309-2/A2 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations |
| Materiale | TERMOPLASTICO | | |
| Grado di protezione generico | Stagno all'immersione | | |
| Grado di protezione IP | IP66/IP67/IP69 | EN 60309-4/A1 (2012) | [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock |
| Grado di protezione IK | IK10 | | |
| Morsetti | Morsetti a vite | DIRECTIVE LOW VOLTAGE 2014/35 /UE | [European Directives] Low Voltage Directive |
| Materiale di contatto | CuZn (ottone) | DIRECTIVE RoHS 2011/65/EU | [European Law] Restriction of the use of certain hazardous substances in electrical and electronic equipment |
| Flangia | 103X230MM | | |

| | |
|---------------|---------------------------|
| Opzioni | Con interblocco meccanico |
| Note | CON BASE PORTAFUSIBILI |
| Tipo fusibile | gG 10,3x38mm |
| Lucchetto | ø5mm |