



# 590.FGE2005.U

## INTERR. DI MANOVRA /SEZIONATORE

20A 3P+N IP65 192x168x80mm GENERALE  
GRIGIO/NERO FIRE RATED 1xNA+1xNC IK10

Certificati

TECHDATA		NORME E LEGGI	
Serie commerciale	Serie ISOLATORS-FR	EN 60947-3 (2009)	[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Tipologia prodotto	INTERR. DI MANOVRA /SEZIONATORE	EN 60947-1 (2007)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Descrizione sintetica	INTERR. DI MANOVRA /SEZIONATORE	EN 60947-1/A1 (2011)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Materiale	LEGA ALLUMINIO PRESSOFUSO	EN 60947-3/A1 (2012)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Grado di protezione IP	IP65	EN 60947-1/A2 (2014)	[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
Tipo	GENERALE	EN 60947-3/A2 (2015)	[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
Colore	GRIGIO/NERO	DIRECTIVE LOW VOLTAGE 2014/35 /UE	[European Directives] Low Voltage Directive
Corrente nominale	20A		
Poli	3P+N		
Dimensioni	192x168x80mm		
Note	FIRE RATED		
Fire rated class	F400 (120min)		
Note1	1xNA+1xNC		
Grado di protezione IK	IK10		