

Article

240.63961T
 APPLIANCE INLET 3P+E IP44/IP54 63A 10h

Picture




Master data


Minimum order	4 NR
Net Weight	0 KG
EAN code	8001636325095
Harmonized System Code (HSCode)	85366990

TechData



Commercial series	OPTIMA-TOP Series
Synthetical description	SURFACE MOUNT. APPLIANCE INLET
Rated current	63A
Poles	3P+E
Hour position	10h
Rated voltage	>50V
Working frequency	100-300Hz
Colour	GREEN
Protection degree IP	IP44/IP54
Types of available outlets	ANGLED
Terminals	Mantle terminals
Cable outlet	M40X1,5

Approvals and Certifications

 UE
 Declaration of conformity

 EAC
 Eurasian Conformity

Standards and Laws

-  EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
-  EN 60309-2 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A2 (2012)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A2 (2012)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations

Packaging

Description	Carton
Quantity	4
EAN code	8001636759531
Gross weight	0 KG
Volume	28533.875 CCM
Dimensions	265x365x295 (MM)

Annexed



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:

- > Cable gland included
- > Threaded cap/cable sleeve included