

Article

513.3253TS
SURF.MNT.SOCKET 2P+E IP44 32A 6h

Picture




Master data


Minimum order	1 NR
Net Weight	0.604 KG
EAN code	8001636306193
Harmonized System Code (HSCode)	85366990

TechData


Commercial series	OPTIMA-TOP Series
Synthetical description	SURFACE MOUNTING SOCKET
Rated current	32A
Poles	2P+E
Hour position	6h
Rated voltage	200-250V
Working frequency	50Hz
Working frequency	60Hz
Colour	BLUE
Protection degree IP	IP44/IP54
Types of available outlets	ANGLED
Terminals	Screw terminals
Cable outlet	M32X1,5


Approvals and Certifications

 UE
Declaration of conformity

 EAC
Eurasian Conformity

Standards and Laws

 EN 60309-1 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements

 EN 60309-2 (1999)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-4 (2007)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock



EN 60309-1/A2 (2012)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A2 (2012)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-4/A1 (2012)
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock

Packaging

Description	Carton
Quantity	6
EAN code	8001636764955
Gross weight	4.764 KG
Volume	36012.5 CCM
Dimensions	250x335x430 (MM)
Description	Box
Quantity	1
EAN code	
Gross weight	0.794 KG
Volume	3833.027 CCM
Dimensions	163x183x128.5 (MM)

Annexed



Technical drawing [DWG]






Technical drawing [PDF]



Technical drawing [STP]

Note:

-  Threaded break-through knock out 

-  Rubber threaded cable sleeve included 