

**Article**

**513.63576T**  
SURF.MNT.SOCKET 3P+N+E IP44 63A 7h

**Picture**




**Master data**


Minimum order	4 NR
Net Weight	0.952 KG
EAN code	8001636337180
Harmonized System Code (HSCode)	85366990

**TechData**



Commercial series	OPTIMA-TOP Series
Synthetical description	SURFACE MOUNTING SOCKET
Rated current	63A
Poles	3P+N+E
Hour position	7h
Rated voltage	480-500V
Working frequency	50Hz
Working frequency	60Hz
Colour	BLACK
Protection degree IP	IP44
Types of available outlets	ANGLED
Terminals	Mantle terminals
Cable outlet	M40X1,5

**Approvals and Certifications**

 UE  
Declaration of conformity

 EAC  
Eurasian Conformity

**Standards and Laws**

-  EN 60309-1 (1999)  
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements
-  EN 60309-2 (1999)  
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)  
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)  
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A2 (2012)  
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A2 (2012)  
[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations

### Packaging

Description	Carton
Quantity	4
EAN code	8001636765457
Gross weight	4.328 KG
Volume	28800 CCM
Dimensions	300x400x240 (MM)

### Annexed



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

### Note:

- > Open threaded cable entry
- > Cable gland included
- > Threaded cap/cable sleeve included