

**Article**

**590.KGEB25005B**  
SWITCH DISCONNECTOR IP65 250A 3P+N

**Picture**




**Master data**


Minimum order	1 NR
Net Weight	0 KG
EAN code	8001636027012
Harmonized System Code (HSCode)	85365080

**TechData**




Commercial series	ISOLATORS Series
Synthetical description	SWITCH DISCONNECTOR
Protection degree IP	IP65
Type	GENERAL
Colour	GREY/BLACK
Rated current	250A
Poles	3P+N
Switch size	KF2
Fuse type	BS
Dimensions	400x600x250mm
Notes	FUSE: BS

**Approvals and Certifications**

 UE  
Declaration of conformity

 EAC  
Eurasian Conformity

**Standards and Laws**

-  EN 60947-3 (2006)  
[European Standard] Low-voltage switchgear and controlgear - Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units
-  EN 60947-1 (2007)  
[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules
-  EN 60947-1/A1 (2011)  
[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules



EN 60947-3/A1 (2011)  
[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units



EN 60947-1/A2 (2014)  
[European Standard] Low-voltage switchgear and controlgear - Part 1: General rules



EN 60947-3/A2 (2015)  
[European Standard] Low-voltage switchgear and controlgear Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units

### Packaging

Description	Carton
Quantity	1
EAN code	
Gross weight	0 KG
Volume	0
Dimensions	0x0x0 ()

### Annexed



Instruction manual



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

### Note:

- > Handle padlockable in OFF only (3 padlocks) x
- > BOTTOM/BOTTOM = Bottom/Bottom connection with busbar x
- > Equipped with door interlock x
- > With late break and early make neutral pole x
- > Gland plate cable entry x
- > Fuses not supplied x