

Load feeder fuseless direct-on-line starting, 400 V AC 80...100 A, 110 V AC 50 Hz Size S3 Screw terminal for installation on standard mounting rail Iq = 50 kA 1 NO + 1 NC (circuit breaker) !!! Phased-out product !!! Successor is SIRIUS 3RA2

product brand name

SIRIUS

Certificates/ approvals

General Product Approval	For use in hazardous locations	Declaration of Conformity	Marine / Shipping
--------------------------	--------------------------------	---------------------------	-------------------



[Miscellaneous](#)



Marine / Shipping	other
-------------------	-------



[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RA1145-6MA45-0AG6>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA1145-6MA45-0AG6>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RA1145-6MA45-0AG6>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA1145-6MA45-0AG6&lang=en

Characteristic: Tripping characteristics, I²t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RA1145-6MA45-0AG6/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RA1145-6MA45-0AG6&objecttype=14&gridview=view1>

last modified:

08/13/2020