

Solid-state contactor 3-phase 3RF2 AC 51 / 30 A / 40 °C 48-600 V /
230 V AC 2-phase controlled screw terminal Blocking voltage 1200 V



Product brand name	SIRIUS
Product designation	solid-state contactor
Product type designation	3RF24

General technical data

Product function	zero-point switching
Power loss [W] / for rated value of the current / at AC / in hot operating state	61 W
Insulation voltage	
• rated value	600 V
Degree of pollution	3
Protection class IP	IP20
Shock resistance / acc. to IEC 60068-2-27	15g / 11 ms
Vibration resistance / acc. to IEC 60068-2-6	2g
Reference code / acc. to DIN EN 81346-2	Q

Main circuit

Number of poles / for main current circuit	3
Number of NO contacts / for main contacts	2
Number of NC contacts / for main contacts	0
Operating voltage / at AC	

<ul style="list-style-type: none"> • at 50 Hz / rated value 	48 ... 600 V
<ul style="list-style-type: none"> • at 60 Hz / rated value 	48 ... 600 V
Operating frequency / rated value	50 ... 60 Hz
Relative symmetrical tolerance / of the operating frequency	10 %
Operating range relative to the operating voltage / at AC	
<ul style="list-style-type: none"> • at 50 Hz 	40 ... 660 V
<ul style="list-style-type: none"> • at 60 Hz 	40 ... 660 V
Operating current	
<ul style="list-style-type: none"> • at AC-51 / rated value 	30 A
<ul style="list-style-type: none"> • acc. to UL 508 / rated value 	22 A
Operating current / minimum	500 mA
Rate of voltage rise / at the thyristor / for main contacts / maximum permissible	1 000 V/ μ s
Blocking voltage / at the thyristor / for main contacts / maximum permissible	1 200 V
Reverse current / of the thyristor	10 mA
Derating temperature	40 °C
Surge current resistance / rated value	1 200 A
I²t value / maximum	7 200 A ² ·s

Control circuit/ Control

Type of voltage / of the control supply voltage	AC
Control supply voltage / 1 / at AC	
<ul style="list-style-type: none"> • at 50 Hz 	180 ... 230 V
<ul style="list-style-type: none"> • at 60 Hz 	180 ... 230 V
Control supply voltage frequency	
<ul style="list-style-type: none"> • 1 / rated value 	45 Hz
<ul style="list-style-type: none"> • 2 / rated value 	66 Hz
Control supply voltage / at AC	
<ul style="list-style-type: none"> • at 50 Hz / Full-scale value for signal<0> recognition 	40 V
<ul style="list-style-type: none"> • at 60 Hz / Full-scale value for signal<0> recognition 	180 V
Control supply voltage	
<ul style="list-style-type: none"> • at AC / initial value for signal <1> detection 	180 V
Symmetrical line frequency tolerance	5 Hz
Control current / at minimum control supply voltage	
<ul style="list-style-type: none"> • at AC 	2 mA
Control current / at AC / rated value	15 mA
Switch-on delay time	40 ms; additionally max. one half-wave
Number of NC contacts / for auxiliary contacts	0
Number of NO contacts / for auxiliary contacts	0

Number of CO contacts / for auxiliary contacts	0
--	---

Installation/ mounting/ dimensions

Mounting type	screw and snap-on mounting onto 35 mm standard mounting rail
<ul style="list-style-type: none"> • Side-by-side mounting 	Yes
Height	100 mm
Width	74.5 mm; 90.5 mm product version E01
Depth	115.6 mm; 112.5 mm product version E01
Installation altitude / at height above sea level / maximum	1 000 m

Connections/ Terminals

Type of connectable conductor cross-sections	
<ul style="list-style-type: none"> • for main contacts <ul style="list-style-type: none"> — solid 	2x (1.5 ... 2.5 mm ²), 2x (2.5 ... 6 mm ²)
<ul style="list-style-type: none"> — finely stranded / with core end processing 	2x (1 ... 2.5 mm ²), 2x (2.5 ... 6 mm ²), 1x 10 mm ²
<ul style="list-style-type: none"> • at AWG conductors / for main contacts 	2x (14 ... 10)
Type of connectable conductor cross-sections	
<ul style="list-style-type: none"> • for auxiliary and control contacts <ul style="list-style-type: none"> — solid 	1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.0 mm ²)
<ul style="list-style-type: none"> — finely stranded / with core end processing 	1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.0 mm ²)
<ul style="list-style-type: none"> — finely stranded / without core end processing 	1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.0 mm ²)
<ul style="list-style-type: none"> • at AWG conductors / for auxiliary and control contacts 	1x (AWG 20 ... 12)
Tightening torque	
<ul style="list-style-type: none"> • for main contacts / with screw-type terminals 	2 ... 2.5 N·m
<ul style="list-style-type: none"> • for auxiliary and control contacts / with screw-type terminals 	0.5 ... 0.6 N·m
Tightening torque [lbf·in]	
<ul style="list-style-type: none"> • for main contacts / with screw-type terminals 	18 ... 22 lbf·in
<ul style="list-style-type: none"> • for auxiliary and control contacts / with screw-type terminals 	7.5 ... 5.3 lbf·in
Design of the thread / of the connection screw	
<ul style="list-style-type: none"> • for main contacts 	M4
<ul style="list-style-type: none"> • of the auxiliary and control contacts 	M3
Wire stripping length / of the cable	
<ul style="list-style-type: none"> • for main contacts 	7 mm
<ul style="list-style-type: none"> • for auxiliary and control contacts 	7 mm

Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> • during operation 	-25 ... +60 °C
<ul style="list-style-type: none"> • during storage 	-55 ... +80 °C

Electromagnetic compatibility

Conducted interference <ul style="list-style-type: none">• due to burst / acc. to IEC 61000-4-4• due to conductor-earth surge / acc. to IEC 61000-4-5• due to conductor-conductor surge / acc. to IEC 61000-4-5• due to high-frequency radiation / acc. to IEC 61000-4-6	2 kV / 5 kHz behavior criterion 2 2 kV behavior criterion 2 1 kV behavior criterion 2 140 dBuV in the frequency range 0.15 ... 80 MHz, behavior criterion 1
Electrostatic discharge / acc. to IEC 61000-4-2	4 kV contact discharging / 8 kV air discharging, behavior criterion 2
Conducted HF-interference emissions / acc. to CISPR11	Class A for industrial environment
Field-bound HF-interference emission / acc. to CISPR11	Class A for industrial environment

Short-circuit protection, design of the fuse link

Manufacturer's article number <ul style="list-style-type: none">• of full range R fuse link for semiconductor protection / at NH design• of full range R fuse link for semiconductor protection / at cylindrical design• of back-up R fuse link for semiconductor protection / at NH design• of back-up R fuse link for semiconductor protection / at cylindrical design 10 x 38 mm• of back-up R fuse link for semiconductor protection / at cylindrical design 14 x 51 mm• of back-up R fuse link for semiconductor protection / at cylindrical design 22 x 58 mm	3NE1803-0 5SE1335; Maximum operating voltage 400 V! 3NE8003-1 3NC1032 3NC1450 3NC2280
Manufacturer's article number / of the gG fuse / at NH design <ul style="list-style-type: none">• up to 460 V	3NA3812

Certificates/ approvals

General Product Approval	EMC	Declaration of Conformity
--------------------------	-----	---------------------------



[Miscellaneous](#)

Test Certificates	other
-------------------	-------

[Type Test Certificates/Test Report](#)

[Confirmation](#)



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RF2430-1AB55>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RF2430-1AB55>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RF2430-1AB55>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RF2430-1AB55&lang=en





