

Power regulator Current range 90 A / 40 °C 400-600 V / 24 V AC/DC for semiconductor relay / contactor



Product brand name	SIRIUS
Product designation	power regulator
Manufacturer's article number	
<ul style="list-style-type: none"> • _1 / of the accessories that can be ordered • _2 / of the accessories that can be ordered 	3RF2900-0RA88 4EU2452-3UA00-0AA0
Product designation	
<ul style="list-style-type: none"> • _1 / of the accessories that can be ordered • _2 / of the accessories that can be ordered 	sealable end cover input reactor / 1AC

General technical data	
Product function	solid-state relay / solid-state contactor 3RF2
Insulation voltage	
<ul style="list-style-type: none"> • rated value 	600 V
Degree of pollution	3
Protection class IP	IP20
Shock resistance / acc. to IEC 60068-2-27	15g / 11 ms
Vibration resistance / acc. to IEC 60068-2-6	2g
Reference code / acc. to DIN EN 81346-2	K

Main circuit

Number of poles / for main current circuit	0
Number of NO contacts / for main contacts	0
Number of NC contacts / for main contacts	0
Operating voltage / at AC	
• at 50 Hz / rated value	400 ... 600 V
• at 60 Hz / rated value	400 ... 600 V
Operating frequency / rated value	50 ... 60 Hz
Relative symmetrical tolerance / of the operating frequency	10 %
Operating range relative to the operating voltage / at AC	
• at 50 Hz	340 ... 660 V
• at 60 Hz	340 ... 660 V
Operating current	
• at AC-51 / rated value	90 A
Derating temperature	40 °C

Control circuit/ Control






Control supply voltage / 1	
• at DC	24 V
Control supply voltage / at AC	
• at 50 Hz / Full-scale value for signal<0> recognition	5 V
• at 60 Hz / Full-scale value for signal<0> recognition	5 V
Control supply voltage	
• at DC / Full-scale value for signal<0> recognition	5 V
Symmetrical line frequency tolerance	5 Hz
Control current / at minimum control supply voltage	
• at AC	2 mA
• at DC	2 mA
Control current / at AC / rated value	40 mA
Control current / at DC / rated value	40 mA
Number of NC contacts / for auxiliary contacts	1
Number of NO contacts / for auxiliary contacts	0
Number of CO contacts / for auxiliary contacts	0

Installation/ mounting/ dimensions

Mounting type	clip-on
• Side-by-side mounting	Yes
Height	111.5 mm
Width	45 mm
Depth	69.5 mm

Installation altitude / at height above sea level / maximum	1 000 m
Connections/ Terminals	
Type of electrical connection	
<ul style="list-style-type: none"> • for auxiliary and control current circuit 	screw-type terminals
Type of connectable conductor cross-sections	
<ul style="list-style-type: none"> • for auxiliary and control contacts <ul style="list-style-type: none"> — solid — finely stranded / with core end processing — finely stranded / without core end processing • at AWG conductors / for auxiliary and control contacts 	1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.0 mm ²) 1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.0 mm ²) 1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.0 mm ²) 1x (AWG 20 ... 12)
Tightening torque	
<ul style="list-style-type: none"> • for auxiliary and control contacts / with screw-type terminals 	0.5 ... 0.6 N·m
Tightening torque [lbf·in]	
<ul style="list-style-type: none"> • for auxiliary and control contacts / with screw-type terminals 	4.5 ... 5.3 lbf·in
Design of the thread / of the connection screw	
<ul style="list-style-type: none"> • of the auxiliary and control contacts 	M3
Wire stripping length / of the cable	
<ul style="list-style-type: none"> • for auxiliary and control contacts 	7 mm
Ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> • during operation • during storage 	-25 ... +60 °C -55 ... +80 °C
Electromagnetic compatibility	
Conducted interference	
<ul style="list-style-type: none"> • due to burst / acc. to IEC 61000-4-4 • due to conductor-earth surge / acc. to IEC 61000-4-5 • due to conductor-conductor surge / acc. to IEC 61000-4-5 • due to high-frequency radiation / acc. to IEC 61000-4-6 	2 kV / 5 kHz behavior criterion 2 2 kV behavior criterion 2 1 kV behavior criterion 2 140 dBuV in the frequency range 0.15 ... 80 MHz, behavior criterion 1
Electrostatic discharge / acc. to IEC 61000-4-2	4 kV contact discharging / 8 kV air discharging, behavior criterion 2
Conducted HF-interference emissions / acc. to CISPR11	Class A for industrial environment
Field-bound HF-interference emission / acc. to CISPR11	Class B for the domestic, business and commercial environments

Certificates/ approvals

General Product Approval		EMC	Declaration of Conformity		
 CSA	 UL		 RCM	 EG-Konf.	Miscellaneous

Test Certificates	other
Type Test Certificates/Test Report	Confirmation

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RF2990-0HA16>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RF2990-0HA16>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RF2990-0HA16>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RF2990-0HA16&lang=en

