

Contactor relay, 40E, EN 50011, 4 NO; Screw terminal AC operation
32 V AC 50 Hz/38 V AC 60 Hz !!! Phased-out product !!! Successor is
SIRIUS 3RH21



Figure similar

product designation	Auxiliary contactor
product type designation	3TH2
Size of contactor	0
protection class IP on the front	IP20
reference code acc. to DIN EN 81346-2	K
<ul style="list-style-type: none"> • ambient temperature during operation 	-25 ... +55 °C
Type of voltage of the control supply voltage	AC
<ul style="list-style-type: none"> • Control supply voltage at AC at 50 Hz rated value 	32 V
<ul style="list-style-type: none"> • Control supply voltage at AC at 60 Hz rated value 	38 V
control supply voltage frequency	
<ul style="list-style-type: none"> • 1 rated value 	50 Hz
<ul style="list-style-type: none"> • 2 rated value 	60 Hz
<ul style="list-style-type: none"> • number of NC contacts for auxiliary contacts 	0
<ul style="list-style-type: none"> • Number of NC contacts for auxiliary contacts delayed switching 	0

<ul style="list-style-type: none"> • Number of NC contacts for auxiliary contacts lagging switching 	0
<ul style="list-style-type: none"> • Number of NC contacts for auxiliary contacts make-before-break switching 	0
<ul style="list-style-type: none"> • number of NO contacts for auxiliary contacts 	4
<ul style="list-style-type: none"> • Number of NO contacts for auxiliary contacts delayed switching 	0
<ul style="list-style-type: none"> • Number of NO contacts for auxiliary contacts leading contact 	0
<ul style="list-style-type: none"> • Number of NO contacts for auxiliary contacts make-before-break switching 	0
number of CO contacts for auxiliary contacts	0
Identification number and letter for switching elements	40 E
Operating current at AC-15	
<ul style="list-style-type: none"> • at 230 V rated value 	4 A
<ul style="list-style-type: none"> • at 400 V rated value 	3 A
mounting type	screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022
height	48 mm
width	45 mm
depth	68 mm
type of electrical connection for auxiliary and control current circuit	screw-type terminals
B10 value with high demand rate acc. to SN 31920	400 000; With 0.3 x Ie
T1 value for proof test interval or service life acc. to IEC 61508	20 y
protection against electrical shock	finger-safe

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TH2040-0AC0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TH2040-0AC0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TH2040-0AC0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TH2040-0AC0&lang=en

Characteristic: Tripping characteristics, I²t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3TH2040-0AC0/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3TH2040-0AC0&objecttype=14&gridview=view1>

last modified:

08/25/2020