



Accessory 3WA/3WL Closing coil (CC) 5% OP, 208-240 V AC / 220-250 V DC momentary duty, with cut-off switch, not for continuous duty

Model	
product brand name	SENTRON
product designation	3WA circuit breaker accessories
design of the product	closing coil (CC) 5% OP, 208 to 240 V AC / 220 to 250 V DC for momentary duty, with cut-off switch, no continuous duty possible
closing apparent power [VA]	250 VA
closing active power [W]	250 W
minimum command time / at $U_s = 100\%$	60 ms
make time / electrical	50 ms
opening time / of circuit breaker / at $U_s = 100\%$	50 ms
control supply voltage (U_s) / at AC / rated value	208 to 240 V 50/60 Hz
design of the DIAZED fuse link gG/miniatuure circuit breaker with tripping characteristic class C 5% / for short-circuit protection / minimum permissible	2 A
ambient temperature / during operation	
• minimum	-40 °C
• maximum	70 °C
ambient temperature / during storage	
• minimum	-40 °C
• maximum	80 °C

General Product Approval

EMC

Declaration of Conformity

Dangerous Good

[Confirmation](#)



[UK Declaration of Conformity](#)



[Transport Information](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WA9111-0AD16>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WA9111-0AD16>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WA9111-0AD16

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



