

Bell transformer, 8VA Primary 230-240 V AC, 50 Hz, secondary 8 V, 12 V AC With PTC fuse, 2MW++



Model	
product brand name	SETRON
Product designation	Bell transformer
Design of the transformer	Standard bell transformer
General technical data	
supplied active power / maximum	8 W
Voltage	
Input voltage	230 V
Output voltage	
• _1 / rated value	8 V
• _2 / rated value	12 V
Dissipation	
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	6 W
Current	
Output current	
• maximum	1 A

- _1 / rated value 1 A
- _2 / rated value 0.6 A

Suitability

Suitability for integration

- surface-mounted installation No
- flush mounting No

Product details

Product component / switch No

Product function

Product function / Thermal protection Yes

Inputs Outputs

property of the output / short-circuit proof Yes

Mechanical Design

Height	64 mm
Width	36 mm
length	90 mm
number of width units	2
Mounting type / Side-by-side mounting	Yes

Certificates

Declaration of Conformity

other

[Confirmation](#)



EG-Konf.

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4AC3208-1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/4AC3208-1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4AC3208-1

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

