

Soft starting device 400 V AC 300-5500W 3PH Overall depth 55 mm



Model	
product brand name	SENTRON
Product designation	Soft-starting device
Design of the product	55 mm
Supply voltage	
type of voltage	AC
Operating voltage / rated value	
• minimum	230 V
• maximum	230 V
Dissipation	
Power loss [W]	4.6 W
Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	4.6 W
Control current	
Control supply voltage	
• at AC / at 50 Hz / rated value / minimum	230 V
• at AC / at 50 Hz / rated value / maximum	230 V
• at AC / at 60 Hz / rated value / minimum	230 V

- at AC / at 60 Hz / rated value / maximum 230 V

Product function

Product function / motor overload protection No

Mechanical Design

Height	90 mm
Width	105 mm
Depth	55 mm
net weight	450 g

Environmental conditions

Ambient temperature / without derating / rated value 55 °C

Certificates

- reference code / acc. to DIN EN 61346-2 Q
- Reference code / acc. to DIN EN 81346-2 Q

**Declaration of Conform-
ity**

other



EG-Konf.

[Environmental Confirmations](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TT3440>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TT3440>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT3440

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

