

Remote control switch Contact for 20 A Voltage 24 V AC 1 NO 1 NC



Model	
product brand name	SETRON
Product designation	Remote control switch
Latching relay design	Mechanical switch
General technical data	
Electrical endurance (switching cycles)	50 000
Pulse duration / minimum	50 ms
Galvanic isolation / between magnet coil and contact	Yes
Switching voltage / of the contacts / at AC / minimum	10 V
Switching current / at AC / per contact / minimum	100 mA
Power loss [V·A] / of magnet coil / with pulse / rated value	18 V·A
Voltage	
Continuous voltage fuse version	Yes
Surge voltage resistance / rated value	3 kV
Supply voltage	400 V
Supply voltage	
type of voltage	AC

Supply voltage / minimum	230 V
Protection class	
Protection class IP	IP20
Switching capacity	
Switching capacity apparent power	
• for fluorescent lamp load with DUO circuit	2 436 V·A
• for fluorescent lamp load with parallel compensation	812 V·A
• for uncompensated fluorescent lamp load	1 100 V·A
Switching capacity current	
• at cos phi 0.6	20 A
• Rated value	20 A
Switching capacity active power / with filament lamp load	4 400 W
Dissipation	
Power loss [W]	
• at 16 A / per contact / rated value	1.5 W
• of magnet coil / with pulse / rated value	13 W
Control current	
Type of voltage	
• of control voltage_1	AC
Control voltage	
• _1 / initial value	207 V
• _1 / Full-scale value	253 V
• _1 / setpoint	24 V
Control voltage frequency	
• _1 / initial value	50 Hz
• _1 / Full-scale value	60 Hz
Product details	
Product component / Switch position indicator	Yes
Number of NC contacts	1
Number of NO contacts	1
Number of CO contacts	0
Product function	
Product function / direct operation	Yes
Number	
Number of terminals	4
Connections	
Connectable conductor cross-section / for flexible conductor / with core end processing	

<ul style="list-style-type: none"> • minimum • maximum 	1 mm ² 10 mm ²
Connectable conductor cross-section / for rigid conductor	
<ul style="list-style-type: none"> • minimum • maximum 	1 mm ² 10 mm ²

Mechanical Design	
Height	90 mm
Width	17.5 mm
Width of opening / of the contacts	3 mm
Depth	73 mm
Mounting height	90 mm
installation depth	73 mm
number of width units	1
Mounting type	DIN rail
mounting position	Horizontal and vertical
net weight	166 g

Environmental conditions	
Ambient temperature	
<ul style="list-style-type: none"> • minimum • maximum 	-25 °C 55 °C

Certificates	
<ul style="list-style-type: none"> • reference code / acc. to DIN EN 61346-2 • Reference code / acc. to DIN EN 81346-2 	K K

Declaration of Conformity	Test Certificates
---------------------------	-------------------



[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TT4405-2>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TT4405-2>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT4405-2

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>





