

INSTA contactor with 4 NO contacts Contact for 230 V AC, 400V 25A
Control 115 V AC



Model	
product brand name	SETRON
Product designation	Insta contactor
Design of the product	4 NO contacts
Type of voltage / of the operating voltage	AC
Type of voltage / of the operating voltage / for actuation	AC
Supply voltage	
Operating current / at AC / rated value	25 A
Operating voltage / rated value	
• minimum	440 V
• maximum	440 V
Protection class	
Protection class IP	IP20
Switching capacity	
Switching capacity active power / with filament lamp load	2 000 W
Dissipation	

Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	2.2 W
---	-------

Main circuit

Operating current / rated value	25 A
---------------------------------	------

Control current

Control supply voltage	
• rated value	115 V
• rated value / maximum	115 V

Product details

Product component / Slide for manual operation	No
Number of NC contacts	0
Number of NO contacts	4
Product extension / can be installed / supplementary devices	Yes

Mechanical Design

Height	90 mm
Width	36 mm
Depth	71 mm
installation depth	0 mm
number of width units	2
net weight	274 g

Certificates

• reference code / acc. to DIN EN 61346-2	Q
• Reference code / acc. to DIN EN 81346-2	Q

General Product Approval	Declaration of Conformity	Test Certificates	other
--------------------------	---------------------------	-------------------	-------



[Miscellaneous](#)



[Special Test Certificate](#)

[Environmental Confirmations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TT5830-1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TT5830-1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT5830-1

Cx-Online-Generator

<http://www.siemens.com/cax>

