SIEMENS

Data sheet

6ED1055-4MH08-0BA0

LOGO! TD Text Display, 6-line, 3 background colors, 2 Ethernet ports, installation accessories for LOGO! 8



Figure similar

Product type designation	TD
Suitability for use	Can be used with LOGO! 8 and higher
Cultubility for use	our be used with 2000: 0 and higher
Display	
Design of display	FSTN
Line display	
Number of lines	6
 Number of characters per line 	20
Backlighting	
Type of backlighting	LED
Control elements	
Keyboard fonts	
System keys	Yes
 Number of configurable system keys 	0
alphanumeric keyboard	No

Wall mounting/direct mounting	No
Supply voltage	
Type of supply voltage	AC/DC
Rated value (DC)	12 V; 12/24 V DC, 24 V AC
Dawer less	
Power loss Power loss, typ.	1.8 W; At 24 V DC
Fower loss, typ.	1.6 W, At 24 V DC
Interrupts/diagnostics/status information	
Diagnostics function	No
Degree and class of protection	
IP (at the front)	IP65
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
FM approval	Yes
KC approval	Yes
Marine approval	
American Bureau of Shipping (ABS)	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	-20 °C; No condensation
• max.	55 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Altitude during operation relating to sea level	
	Tmin Tmax at 1 080 hPa 795 hPa (-1 000 m +2 000 m)
 Ambient air temperature-barometric pressure- altitude 	1111111 1111ax at 1 000 111 a 133 111 a (-1 000 111 12 000 111)
Configuration	
Configuration software	
Configuration tool	LOGO! Soft Comfort V8
Accessories	
belongs to product	LOGO!
Mechanics/material	
Design of housing	plastic
Dimensions	
Width	128.2 mm
Height	86 mm
Depth	38.7 mm
Overall depth	38.7 mm

Weights	
Weight, approx.	220 g
Scope of supply	
Delivery quantity in pieces	1
last modified:	08/25/2020