

SIMATIC NET, Repeater for AS-Interface for cable extension in K45 enclosure



General technical data		
Design of the product		AS-Interface Repeater
Design of the slave type		no slave integrated
Voltage supply using AS-Interface		Yes
Operating voltage acc. to AS Interface specification	V	26.5 ... 31.6
Status display		
<ul style="list-style-type: none"> • U AS-Interface 		green LED
Connections/ Terminals		
Design of the AS-Interface connection		Direct connection to AS-i ribbon cable
AS interface		
<ul style="list-style-type: none"> • Connection Polarity reversal protection 		yes
<ul style="list-style-type: none"> • total current input max 	mA	20
Ambient conditions		
Ambient temperature during operation	°C	-25 ... +60
Protection class IP		IP67
Certificates/ approvals		

General Product Approval

EMC

Declaration of Conformity



CSA



UL



RCM



EG-Konf.

[Miscellaneous](#)

other

[Confirmation](#)



ASi

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=6GK1210-0SA01>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=6GK1210-0SA01>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/6GK1210-0SA01>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=6GK1210-0SA01&lang=en

last modified:

03/06/2020