


## APM 48/63

Adaptor polyamide, RAL 7035, Pg48 / M63



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.



<b>Material</b>	Polyamide, fibre reinforced
<b>Temp. range min</b>	-40 °C
<b>Temp. range max</b>	100 °C
<b>Glow wire test</b>	650 °C
<b>Thread type outer</b>	PG
<b>Ø outer thread</b>	48
<b>Length screw-in thread L</b>	15 mm
<b>Thread type inner</b>	M
<b>Ø inner thread</b>	63
<b>Lead inner</b>	1,5
<b>Length internal thread</b>	15,5 mm
<b>Total length TL</b>	33 mm
<b>Key width SW</b>	68 mm
<b>Collar diameter (E)</b>	72 mm
<b>Form</b>	A
<b>Product Color</b>	RAL 7035
<b>Order no. RAL 7035</b>	10063677
<b>Type</b>	APM 48/63
<b>Packing unit</b>	5
<b>ETIM-Classification</b>	EC000938

### Recommended accessories

<b>MUG 48</b>	10060679
---------------	----------

Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

14.01.2021


Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com